## MEASURING DEVICE FOR POSITION OF ASSEMBLED PIPING

Patent number:

JP58015108

**Publication date:** 

1983-01-28

Inventor:

YAMADA MASATOSHI; SHIMOYAMA HIROSHI; IIDA

YASUHISA

Applicant:

MITSUBISHI HEAVY IND LTD

Classification:

- international:

G01B5/00; G01B21/00; G01B21/20

- european:


G01B21/22

Application number: JP19810113269 19810720 Priority number(s): JP19810113269 19810720

Report a data error here

## Abstract of JP58015108

PURPOSE: To improve the accuracy of measuring work and to automate the same in the measurement of positions of assembled pipings by using a probe which is movable to the arbitrary position over the space, a measuring jig for the end face of pipings and a correcting means for the deviation in position from the probe. CONSTITUTION: A discoid jig 8 having a part 8a to be fitted consisting of a circular columnar projection is jixed to the end face of a piping 2. A manipulator 1 is fixed to the working floor, and the fitting part 5a of a probe 5 mounted thereto via flexing arms 3 is fitted onto said part 8a. The angles alpha, beta, gamma of the flexing arms are detected with angle detectors 4, and from these angles and the length of the flexing arms, the central coordinate in the fitting part is obtd. Despite the mis-alignment in the centers of the fitting part and the part to be fitted, the distances a-d from the distance detectors 6 provided in the inside circumference of the fitting part up to the outside circumferential surface of the part to be fitted are obtained. The rates of deviation DELTAX, DELTAY of both centers are calculated by using said distances, whereby the information on the position of the leading end of the probe is corrected.



Data supplied from the **esp@cenet** database - Worldwide